



| | 70 Km/h | 80 Km/h | 50 Km/h | 40 Km/h |
|-------------------|-----------|-----------|-----------|-----------|
| PTIMA Total: | 77.900 Kg | 79.100 Kg | 86.000 Kg | 91.200 Kg |
| PTIMA SF Ruedas: | 35.000 Kg | 35.000 Kg | 35.000 Kg | 35.000 Kg |
| PTIMA Suspensión: | 42.900 Kg | 44.100 Kg | 45.000 Kg | 46.200 Kg |
| PTIMA Eje: | 14.300 Kg | 14.700 Kg | 15.000 Kg | 15.400 Kg |
| Tona aprox: | 24.500 Kg | 24.500 Kg | 24.500 Kg | 24.500 Kg |
| Carga útil aprox: | 53.400 Kg | 54.600 Kg | 55.500 Kg | 56.700 Kg |

| INDICE | MODIFICACION | MADURNA | PROGRAMA |
|-----------|--------------|------------------------------------|------------------------------|
| REVISION | Fecha | Dibujado | Material |
| 1/0/0/0 | | | RESO |
| Exécutivo | Comprobado | DESIGNACION | TOLERANCIAS SEGUN ISO 2768-M |
| | | GRSED3 ensanche lateral hidráulico | |
| | | OBSERVACIONES: | |
| | | 2850 - 8350 - E5000 - C00 | |



Este plan es propiedad de CONCRETOS SOLUCIONES S.L. Cualquier préstamo su copia o reproducción sin autorización del propietario.